

Section 1. Identification

Product identifier

Product Identity	Styrene Monomer 50ppm
Other means of	Cinnamene, Cinnamenol; Diarex HF 77; Ethenylbenzene; NCI-
identification	C0220; Pheneth

Relevant identified uses of the substance or mixture and uses advised against

Industrial Use Only

Details of the supplier of the safety data sheet

Company Name	Silver Fern Chemical, Inc. 121 W. De La Guerra Street, Suite B Santa Barbara, CA 93101 USA Customer Service: 1-866-282-3384 / info@silverfernchemical.com
_	Website - www.silverfernchemical.com
Emergency	
24 hour Emergency	Emergency telephone number
Telephone No.	Infotrac: 1-800-535-5053; Outside USA & Canada +1-352- 323-3500

Customer Service:



Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Flammable Liquid, category 3;H226 Acute toxicity(inhalation), category 4;H332 Skin corrosion/irritation category 2;H315 Serious eye damage / eye irritation, category 2A;H319	Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. y Causes serious eye irritation.
Reproductive toxicity, category 2;H361D Specific target organ toxicity, Single exposure category 3;H335	Suspected of damaging the unborn child. May cause respiratory irritation.
Specific target organ toxicity, repeated exposure category 1;H372	Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (hearing organs)
Aspiration hazard, category 1;H304 Aquatic toxicity (chronic), category 3;H412	May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Label elements







Danger

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.



Silver Fern Chemical, Inc. Safety Data Sheet Styrene Monomer 50ppm

H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

[Prevention]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground, bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use only non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe dust, fume, mist, vapors or spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

[Response]

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician. P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313 IF exposed or concerned: Get medical advice or attention.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P314 Get Medical advice or attention if you feel unwell.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical attention.

P337+313 If eye irritation persists: Get medical advice or attention.

P362+364 Take off contaminated clothing and wash it before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]

P403+233 Store in a well ventilated place. Keep container tightly closed.

P403+235 Store in a well ventilated place. Keep cool.
P405 Store locked up.
[Disposal]
P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals. This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per US or Canadian regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Styrene	80 - 100	Flammable Liquid, category 3;H226	
CAS Number: 100-42-5		Acute toxicity(inhalation), category 4;H332	N
Synonyms: Benzene, ethenyl-		Skin corrosion/irritation category 2;H315	No data available
		Serious eye damage / eye irritation, category 2;H319	
		Reproductive toxicity, category 2;H361D	
		Specific target organ toxicity, repeated exposure category 1;H372	
		Specific target organ toxicity, Single exposure category 3;H335	
		Aspiration hazard, category 1;H304	
		Aquatic toxicity (chronic), category 3;H412	

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.



Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

- **Eyes** Rinse with plenty of clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Reproductive or genetic defect hazard. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

- **Inhalation** Harmful if inhaled. May cause respiratory irritation. May be fatal if swallowed and enters airways.
- **Eyes** Causes serious eye irritation.
- Skin Causes skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide. Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed. Keep cool.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapors or spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

128P

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.



Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value	
100-42-5	Styrene	OSHA	100 ppm C 200 ppm	
		ACGIH	10 ppm 20 ppm	
		NIOSH	TWA 50 ppm (215 mg/m ³) STEL: 100 ppm (425 mg/m ³)	

Exposure controls Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators. Eyes Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.



Skin	Avoid skin contact. Wear PVC or rubber gloves to keep skin contact to a minimum. Refer to the manufacturer's recommendations regarding the suitability of any gloves used.
Engineering	Provide adequate ventilation. Where reasonably practicable this should be
Controls	achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work	Use good personal hygiene practices. Wash hands before eating, drinking,
Practices	smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State Color Odor Melting point / freezing point	Liquid Clear, Colorless to Yellow Aromatic -23.8°F (-30.6°C)
Initial boiling point and boiling range	145°C (293°F)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive	Lower Explosive Limit: 1.1%
limits	
	Upper Explosive Limit: 6.1%
Flash Point	31°C (87.8°F)
Auto-ignition temperature	Not spontaneously flammable
Decomposition temperature	No available information
рН	No available information
Viscosity (cSt)	0.762 Centipoise (cPa, cP) or mPas @20C (68F)
Solubility in Water	Soluble
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	5 mmHg (torr) @20°C (68°F)

SILVER FERN

Silver Fern Chemical, Inc. Safety Data Sheet Styrene Monomer 50ppm Revision Date: 05/30/2025

Relative Density Vapor Density

Evaporation rate (Ether = 1) VOC Content Oxidising properties Explosive properties 0.905 3.6 (Air=1)

0.49n-Butyl Acetate=1 100% (7.25/gal) No available information No available information

Other information

No other relevant information.

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur. **Chemical stability** Stable under normal circumstances. **Possibility of hazardous reactions** No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue,



muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Styrene - (100-42-5)	2,650.00, Rat - Category: 5	No data available.	12.00, Rat - Category: 4	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value	
100-42-5	Styrene	OSHA	Regulated Carcinogen: No;	
		NTP	(nown: No; Suspected: Yes;	
		IARC	Group 1: No; Group 2a: Yes; Group 2b: No; Group 3: No;	
		ACGIH	A3	

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)	4	Harmful if inhaled.
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye	2A	Causes serious eye irritation.
damage/irritation		
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity	2	Suspected of damaging the unborn child.
STOT-single exposure		Not Applicable
STOT-single exposure	3	May cause respiratory irritation.
STOT-repeated exposure	1	Causes damage to organs through prolonged or
		repeated exposure.



Possible routes of entry: No available information

Symptoms and effects, both acute and delayed:

Reproductive or genetic defect hazard. Treat symptomatically.

Eyes Causes serious eye irritation.

Skin Causes skin irritation.

Section 12. Ecological information

Toxicity

Harmful to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/L	mg/L	mg/L
Styrene - (100-42-5)	4.08, Pimephales promelas	4.70, Daphnia magna	No data available.

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information



Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA	
UN number	UN2055	UN2055	UN2055	
UN proper	UN2055,Styrene monomer,	Styrene Monomer,	Styrene Monomer,	
shipping name	stabilized,3,III	Stabilized	Stabilized	
Transport hazard Class:3		Class:3	Class:3	
class(es)	Sub Class:Not Applicable	Sub Class:Not	Sub Class:Not	
		Applicable	Applicable	
Packing group	III	III	III	

Environmental hazards

IMDG Marine Pollutant: No; Special precautions for user

No available information

Section 15. Regulatory information

RegulatoryThe regulatory data in Section 15 is not intended to be all-inclusive, onlyOverviewselected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0000100-42-5	Styrene	Yes		ACTIVE

The following flags are used:

•Active - indicates commercial status designation of active

•E - indicates a substance that is the subject of a Section 5(e) Consent Order under TSCA.

•F - indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

•N - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

•P - indicates a commenced Premanufacture Notice (PMN) substance.

 $\bullet R$ - indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

•S - indicates a substance that is identified in a final Significant New Uses Rule.

•SP - indicates a substance that is identified in a proposed Significant New Uses Rule.

•T - indicates a substance that is the subject of a final Section 4 test rule under TSCA.

•UVCB Chemical Substances of Unknown or Variable Composition, Complex Reaction Products and Biological Materials •XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

•Y1 - indicates a polymer that has a number-average molecular weight greater than 1,000 and that was exempt under the 1984 polymer exemption rule.

•Y2 - indicates a polymer that is a polyester and that was exempt under the 1984 polymer exemption rule.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Styrene

Proposition 65 - Carcinogens (>0.0%):

Styrene



Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

WARNING: This product can expose you to chemicals including [Styrene], which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Mass RTK Substances (>1%) :

Styrene

New Jersey RTK Substances (>1%):

Styrene

Pennsylvania RTK Substances (>1%):

Styrene

OSHA Process Safety Management Standard Highly Hazardous Chemicals, Toxics and Reactives:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

US EPA List of Regulated Substances under the Risk Management Plan (RMP) Program:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



US EPA Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) under the Minimum Risk Exemption:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

U.S. - DEA List II or Essential Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

U.S. - DEA - Exempt Chemical Mixtures - List 1 and 2:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

US DHS Chemical Facility Anti-Terrorism Standards (CFATS):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 311/312 Chemicals and RQs (lbs):

Styrene (1,000.00)

Section 16. Other information

Revision Date

05/30/2025

DISCLAIMER OF RESPONSIBILITY

The information on this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume damage or expense arising out of or in any way responsibility and expressly disclaim liability for loss, connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable.



The full text of the phrases appearing in section 3 is:

- H226 Flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

End of Document