



SAFETY DATA SHEET

Silver Fern Chemical, Inc.
Triethanolamine 99%, LFG 85
(Low-Freeze Grade)

Issue Date: 12/03/2019
Print Date: 12/04/2019

Silver Fern Chemical, Inc. encourages and expects you to read and understand the entire SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: Triethanolamine 99%, LFG 85 (Low-Freeze Grade)

Recommended use of the chemical and restrictions on use

Identified uses: For industrial use only. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

COMPANY IDENTIFICATION

Silver Fern Chemical, Inc.
2226 Queen Anne Avenue North
Seattle WA 98109, USA
Customer Service: 1-866-282-3384 / info@silverfernchemical.com

EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Contact
Infotrac 1-800-535-5053 (USA & Canada)
Outside USA & Canada 1-352-323-3500

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200
Not a hazardous substance or mixture.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component

CASRN

Concentration

Triethanolamine	102-71-6	>= 84.0 - <= 86.0 %
Water	7732-18-5	>= 14.0 - <= 16.0 %
N,N-Diethanolamine	111-42-2	< 0.43 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water fog or fine spray.. Dry chemical fire extinguishers.. Carbon dioxide fire extinguishers.. Foam.. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective..

Unsuitable extinguishing media: Do not use direct water stream.. May spread fire..

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.. Combustion products may include and are not limited to:.. Nitrogen oxides.. Carbon monoxide.. Carbon dioxide.. Carbon oxides. Nitrogen oxides (NOx).

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation.. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids..

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles.. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container.. Burning liquids may be extinguished by dilution with water.. Do not use direct water stream. May spread fire.. Move container from fire area if this is possible without hazard.. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage..

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).. Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location.. For protective equipment in post-fire or non-fire clean-up situations, see Section 8 of the safety data sheet..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Large spills: Dike area to contain spill. Pump into suitable and properly labeled containers. Small spills: Dilute with water. Recover spilled material if possible. Absorb with materials such as: Non-combustible material. Sand. Remove with shovel. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes. Wash thoroughly after handling. Thaw and mix well before using. Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancer-causing nitrosamines could be formed. Spills of these organic

materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Avoid freezing. Store under an oxygen-free nitrogen atmosphere. Store in a dry place. Do not store in: Copper. Copper alloys. Galvanized containers.

Storage stability

Storage temperature: > 16 °C (> 61 °F)

Bulk 6 Month

Drum 24 Month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Triethanolamine	ACGIH	TWA	5 mg/m ³
	Further information: eye irr: Eye irritation; skin irr: Skin irritation		
N,N-Diethanolamine	Distributor IHG	TWA	0.2 mg/m ³
	Further information: SKIN: Absorbed via skin		
	ACGIH	TWA Inhalable fraction and vapor	1 mg/m ³
	Further information: liver dam: Liver damage; kidney dam: Kidney damage; A3: Confirmed animal carcinogen with unknown relevance to humans; Skin: Danger of cutaneous absorption		

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Avoid gloves made of: Polyvinyl alcohol ("PVA"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Liquid.
Color	Colorless to yellow
Odor	Ammoniacal
Odor Threshold	No test data available
pH	No test data available
Melting point/range	Not applicable
Freezing point	-5 °C (23 °F) <i>Literature</i>
Boiling point (760 mmHg)	119.1 °C (246.4 °F) <i>Literature</i>
Flash point	closed cup 179 °C (354 °F) <i>Estimated.</i>
Evaporation Rate (Butyl Acetate = 1)	0.9 <i>Estimated.</i>
Flammability (solid, gas)	Not applicable to liquids
Flammability (liquids)	Not expected to be a static-accumulating flammable liquid.
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	9.7 mmHg at 20 °C (68 °F) <i>Literature</i>
Relative Vapor Density (air = 1)	2.5 <i>Calculated.</i>
Relative Density (water = 1)	1.123 at 20 °C (68 °F) / 20 °C <i>Estimated.</i>
Water solubility	at 20 °C (68 °F) <i>Literature</i> completely miscible
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Dynamic Viscosity	40 cP at 50 °C (122 °F) <i>Estimated.</i>
Kinematic Viscosity	No test data available
Explosive properties	No data available
Oxidizing properties	No data available
Molecular weight	No data available
Molecular formula	Not Applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.



10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with: Nitrites. Strong acids. Strong oxidizers. Product may potentially react with various halogenated organic solvents, resulting in temperature and/or pressure increases. Avoid contact with metals such as: Zinc. Galvanized metals. Heating above 60°C in the presence of aluminum can result in corrosion and generation of flammable hydrogen gas. Avoid unintended contact with: Halogenated hydrocarbons.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials..

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, 6,400 mg/kg

Information for components:

Triethanolamine

LD50, Rat, 6,400 mg/kg

N,N-Diethanolamine

LD50, Rat, male and female, 1,600 mg/kg OECD 401 or equivalent

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.



Based on information for component(s):

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Information for components:

Triethanolamine

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

N,N-Diethanolamine

LD50, Rabbit, male, > 8,200 mg/kg

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous.

As product: The LC50 has not been determined.

Information for components:

Triethanolamine

Based on the available data, respiratory irritation was not observed. No deaths occurred following exposure to a saturated atmosphere.

N,N-Diethanolamine

LC0, Rat, male, 4 Hour, Aerosol, 3.35 mg/l

Skin corrosion/irritation

Based on product testing:

Brief contact is essentially nonirritating to skin.

Repeated exposure may cause irritation, even a burn.

Information for components:

Triethanolamine

Brief contact is essentially nonirritating to skin.

Repeated exposure may cause irritation, even a burn.

N,N-Diethanolamine

Prolonged contact may cause skin irritation with local redness.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

May cause more severe response if skin is abraded (scratched or cut).

Not classified as corrosive to the skin according to DOT guidelines.

Serious eye damage/eye irritation

Based on product testing:

May cause slight eye irritation.

Corneal injury is unlikely.

Information for components:

Triethanolamine



May cause slight eye irritation.
Corneal injury is unlikely.

N,N-Diethanolamine

May cause severe eye irritation.
May cause severe corneal injury.

Sensitization

For the major component(s):

Skin contact may cause an allergic skin reaction in a small proportion of individuals.
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

Triethanolamine

Skin contact may cause an allergic skin reaction in a small proportion of individuals.
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

N,N-Diethanolamine

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Information for components:

Triethanolamine

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

N,N-Diethanolamine

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Triethanolamine

Based on physical properties, not likely to be an aspiration hazard.

N,N-Diethanolamine

Based on physical properties, not likely to be an aspiration hazard.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Information for components:

Triethanolamine

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

N,N-Diethanolamine

Results from repeated exposure tests on diethanolamine in laboratory animals include anemia (rats) and effects on kidney (rats and mice) and liver (mice). Heart and nervous system effects were also observed in animals given exaggerated doses of diethanolamine. Changes in other organs, causes of which are nonspecific, were judged secondary to the poor health of the animals due to the extremely high doses of diethanolamine given.

Carcinogenicity

Based on information for component(s): Triethanolamine. Findings from a chronic skin painting study by NTP include liver tumors in mice. Mechanistic studies indicate that tumor formation is of questionable relevance to humans. Findings from a chronic diethanolamine skin painting study by NTP include liver and kidney tumors in mice; no tumors were observed in rats. Mechanistic studies indicate that tumor formation is of questionable relevance to humans. A number of factors may have influenced the results and are being considered in their interpretation.

Information for components:

Triethanolamine

Findings from a chronic skin painting study by NTP include liver tumors in mice. Mechanistic studies indicate that tumor formation is of questionable relevance to humans. Is not classified as a human carcinogen.

N,N-Diethanolamine

Findings from a chronic diethanolamine skin painting study by NTP include liver and kidney tumors in mice; no tumors were observed in rats. Mechanistic studies indicate that tumor formation is of questionable relevance to humans. A number of factors may have influenced the results and are being considered in their interpretation.

Carcinogenicity

Component
N,N-Diethanolamine

List
IARC

ACGIH

Classification
Group 2B: Possibly carcinogenic to humans
A3: Confirmed animal carcinogen with unknown relevance to humans.

Teratogenicity

For the major component(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. However, the relevance of this to humans is unknown. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

Information for components:



Triethanolamine

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. However, the relevance of this to humans is unknown. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

N,N-Diethanolamine

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

Reproductive toxicity

No relevant data found.

Information for components:**Triethanolamine**

No relevant data found.

N,N-Diethanolamine

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. Repeated excessive exposures to high amounts may cause effects on testes and fertility in males.

Mutagenicity

In vitro genetic toxicity studies were negative.

Information for components:**Triethanolamine**

In vitro genetic toxicity studies were negative.

N,N-Diethanolamine

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity**Triethanolamine****Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
May increase pH of aquatic systems to > pH 10 which may be toxic to aquatic organisms.
LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 11,800 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Ceriodaphnia dubia (water flea), static test, 48 Hour, 609.9 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, alga *Scenedesmus* sp., static test, 72 Hour, Growth rate inhibition, 512 mg/l, OECD Test Guideline 201 or Equivalent, Test substance: Neutralised product

Toxicity to bacteria

EC50, activated sludge, 3 Hour, > 1,000 mg/l, OECD 209 Test

Chronic toxicity to aquatic invertebrates

NOEC, *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 16 mg/l

N,N-Diethanolamine**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

May increase pH of aquatic systems to > pH 10 which may be toxic to aquatic organisms.

LC50, *Pimephales promelas* (fathead minnow), static test, 96 Hour, 1,460 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), static test, 48 Hour, 55 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, *Pseudokirchneriella subcapitata* (green algae), 96 Hour, Growth rate inhibition, 2.2 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Growth rate inhibition, 0.6 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Respiration inhibition, 3 Hour, > 1,000 mg/l, activated sludge test (OECD 209)

Chronic toxicity to aquatic invertebrates

NOEC, *Daphnia magna* (Water flea), semi-static test, 21 d, 0.78 mg/l

Persistence and degradability**Triethanolamine**

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 97 %

Exposure time: 28 d

Method: OECD Test Guideline 301A or Equivalent

10-day Window: Not applicable

Biodegradation: 89 %

Exposure time: 14 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 2.04 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals
Atmospheric half-life: 0.097 d
Method: Estimated.

N,N-Diethanolamine

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 93 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 2.13 mg/mg

Chemical Oxygen Demand: 1.33 mg/mg Dichromate

Photodegradation
Test Type: Half-life (indirect photolysis)
Sensitization: OH radicals
Atmospheric half-life: 0.167 d
Method: Estimated.

Bioaccumulative potential

Triethanolamine

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): -2.3 at 25 °C Measured
Bioconcentration factor (BCF): < 3.9 Cyprinus carpio (Carp) 42 d Measured

N,N-Diethanolamine

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): -2.18 at 25 °C OECD Test Guideline 107 or Equivalent

Mobility in soil

Triethanolamine

Potential for mobility in soil is very high (Koc between 0 and 50).
Partition coefficient (Koc): 10 Estimated.

N,N-Diethanolamine

Potential for mobility in soil is very high (Koc between 0 and 50).
Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.
Partition coefficient (Koc): 1 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and



compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.(Diethanolamine)
UN number	UN 3082
Class	9
Packing group	III
Reportable Quantity	Diethanolamine

Classification for SEA transport (IMO-IMDG):

	Not regulated for transport
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

No SARA Hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



Pennsylvania Worker and Community Right-To-Know Act:

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Triethanolamine	102-71-6

California Prop. 65

WARNING: This product can expose you to chemicals including N,N-Diethanolamine, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact. Additional information on this and other products may be obtained by visiting our web page.

Hazard Rating System**NFPA**

Health	Flammability	Instability
1	1	0

Revision

Identification Number: 371985 / A001 / Issue Date: 12/03/2019 / Version: 12.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Distributor IHG	Distributor Industrial Hygiene Guideline
TWA	8-hour, time-weighted average

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International



Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

DISCLAIMER OF RESPONSIBILITY

The information on this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable.

<end of document>

