

Revision Date: 05/30/2025

Section 1. Identification

Product identifier

Product IdentityKeroseneOther means of identificationNot Applicable

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name Silver Fern Chemical, Inc.

121 W. De La Guerra Street, Suite B Santa Barbara, CA 93101 USA Customer Service: 1-866-282-3384/

info@silverfernchemical.com

Website - www.silverfernchemical.com

Emergency

24 hour Emergency Emergency telephone number

Telephone No. Infotrac: 1-800-535-5053; Outside USA & Canada +1-352-

323-3500

Customer Service:

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Flammable Liquid, category 3;H226

Flammable liquid and vapor.



Revision Date: 05/30/2025

Label elements



H226 Flammable liquid and vapor.

[Prevention]

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground, bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use only non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves, eye protection, and face protection.

[Response]

P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]

P403+235 Store in a well ventilated place. Keep cool.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per US or Canadian regulations.



Revision Date: 05/30/2025

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Kerosene (petroleum)	80 - 100	Aspiration hazard, category 1;H304	
CAS Number: 8008-20-6			No data available
Synonyms: Kerosine (petroleum)			No data avaitable

The actual concentration or concentration range is withheld as a trade secret.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position

and obtain immediate medical attention. Give nothing by mouth.

Eyes Rinse with plenty of clean water for at least 15 minutes, holding the eyelids

apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or

use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce

vomiting.

Most important symptoms and effects, both acute and delayed

Overview No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in

^{*}PBT/vPvB - PBT, vPvM or vPvB-substance.



drowsiness and in extreme cases, loss of consciousness.

adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness,

Revision Date: 05/30/2025

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed.

Keep cool.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No. 128



Section 6. Accidental release measures

Revision Date: 05/30/2025

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]

occount 2 for farther detaile. [eterage

Specific end use(s)

No available information



Revision Date: 05/30/2025

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
8008-20-6	Kerosene (petroleum)	OSHA	No Established Limit
		ACGIH	200 mg/m³(P) Aerosol
		NIOSH	TWA 100 mg/m ³

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must

use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Provide adequate ventilation. Where reasonably practicable this should be

Controls achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection

must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking,

Practices smoking or using toilet. Promptly remove soiled clothing and wash

thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State Liquid

Color Water white to pale yellow

Odor Petroleum distillate



limits

Melting point / freezing point

Flammability (solid, gas)

Initial boiling point and boiling range

Upper/lower flammability or explosive

Silver Fern Chemical, Inc. Safety Data Sheet Kerosene

-4 °F (-20 °C)

300 to 580 °F (149 to 304 °C)

Not Applicable

Lower Explosive Limit: No available

Revision Date: 05/30/2025

information

Upper Explosive Limit: No available

information

Flash Point 100.4 – 125.6 °F (38 -52 °C)

Auto-ignition temperature 410 °F (210 °C)

Decomposition temperatureWhen heated it emits acrid smoke and

irritating vapors.

pH No available information

Viscosity (cSt)

Solubility in Water

Partition coefficient n-octanol/water

1.39 – 1.50 mm2/x (40C)

No available information

No available information

(Log Kow)

Vapor pressure (Pa) 0.480 mm Hg @ 20 °C

Relative Density 0.80 to <1.0

Vapor Density 4.5

Partition coefficient: n-octanol/water Log Kow range of 3.3 to >.6.0

Evaporation rate (Ether = 1)Slow, varies with conditionsOxidising propertiesNo available informationExplosive propertiesNo available information

Flammability Flammable Limits - 0.7 % - 5.0%

Solubility Insol in water; miscible with other petroleum

solvents.

Other information

No other relevant information.

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.



Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Revision Date: 05/30/2025

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Kerosene (petroleum) - (8008-	> 5,000.00, Rat -	>2,000.00, Rabbit -	No data	No data	No data
20-6)	Category: NA	Category: 5	available.	available.	available.



Revision Date: 05/30/2025

Carcinogen Data

CAS No.	Ingredient	Source	Value
8008-20-6	Kerosene (petroleum)	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	A3

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry: No available information

Symptoms and effects, both acute and delayed:

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/L	mg/L	mg/L
Kerosene (petroleum) - (8008-20-6)			



Revision	Date: 0	5/30/2025
----------	---------	-----------

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/L	mg/L	mg/L
	5.00, Oncorhynchus mykiss	1.40, Daphnia magna	3.00, Pseudokirchneriella subcapitata

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface	IMO / IMDG (Ocean	ICAO/IATA
	Transportation)	Transportation)	
UN number	UN1223	UN1223	UN1223
UN proper	UN1223,Kerosene,3,III	Kerosene	Kerosene
shipping name			
Transport	Class:3	Class:3	Class:3
hazard class(es)	Sub Class:Not Applicable	Sub Class:Not	Sub Class: Not
		Applicable	Applicable
Packing group	III	III	III

Environmental hazards

IMDG Marine Pollutant: No;



Revision Date: 05/30/2025

Special precautions for user

No available information

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0008008-20-6	Kerosene (petroleum)	Yes	UVCB	ACTIVE
0000091-20-3	Naphthalene	Yes		ACTIVE

The following flags are used:

- Active indicates commercial status designation of active
- •E indicates a substance that is the subject of a Section 5(e) Consent Order under TSCA.
- •F indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- •N indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- •P indicates a commenced Premanufacture Notice (PMN) substance.
- •R indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S indicates a substance that is identified in a final Significant New Uses Rule.
- •SP indicates a substance that is identified in a proposed Significant New Uses Rule.
- •T indicates a substance that is the subject of a final Section 4 test rule under TSCA.
- •UVCB Chemical Substances of Unknown or Variable Composition, Complex Reaction Products and Biological Materials •XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
- •Y1 indicates a polymer that has a number-average molecular weight greater than 1,000 and that was exempt under the 1984 polymer exemption rule.
- •Y2 indicates a polymer that is a polyester and that was exempt under the 1984 polymer



Revision Date: 05/30/2025

exemption rule.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

Naphthalene

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:



WARNING: This product can expose you to chemicals including [Naphthalene], which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Mass RTK Substances (>1%):

Kerosene (petroleum)

New Jersey RTK Substances (>1%):

Kerosene (petroleum)



Pennsylvania RTK Substances (>1%):

Kerosene (petroleum)

OSHA Process Safety Management Standard Highly Hazardous Chemicals, Toxics and Reactives:

Revision Date: 05/30/2025

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

US EPA List of Regulated Substances under the Risk Management Plan (RMP) Program:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

US EPA Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) under the Minimum Risk Exemption:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

U.S. - DEA List II or Essential Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

U.S. - DEA - Exempt Chemical Mixtures - List 1 and 2:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

US DHS Chemical Facility Anti-Terrorism Standards (CFATS):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Section 16. Other information

Revision Date

05/30/2025

Revision Date: 05/30/2025

DISCLAIMER OF RESPONSIBILITY

The information on this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume damage or expense arising out of or in any way responsibility and expressly disclaim liability for loss, connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

End of Document