

SILVER FERN CHEMICAL, INC.

Safety Data Sheet Morpholine

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Morpholine

CAS-No. : 110-91-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Chemical for synthesis

1.3 Details of the supplier of the safety data sheet

Company : Silver Fern Chemical, Inc.

121 W. De La Guerra Street, Suite B Santa Barbara, CA 93101 USA

Customer Service : +1 866-282-3384 / info@silverfernchemical.com

1.4 24 Hour Emergency Telephone

: Infotrac: 1-800-535-5053 (USA & Canada) Outside USA & Canada 1-352-323-3500

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311 Skin corrosion (Category 1B), H314 Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Danger

Hazard statement(s) H226 H302 H311 + H331 H314	Flammable liquid and vapor. Harmful if swallowed. Toxic in contact with skin or if inhaled. Causes severe skin burns and eye damage.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 +	IF IN EYES: Rinse cautiously with water for several minutes.
P310	Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant
1370 1 1370	foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : C4H9NO Molecular weight : 87.12 g/mol CAS-No. : 110-91-8 EC-No. : 203-815-1 Index-No. : 613-028-00-9

Component	Classification	Concentration					
Tetrahydro-2H-1,4-oxazine							
	Flam. Lig. 3; Acute Tox.	4; <= 100 %					



Acute Tox. 3; Skin Corr. 1B; Eye Dam. 1; H226, H302, H331, H311, H314,	
H318	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aider needs to protect himself. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NOx)

Combustible.

Fire may cause evolution of:

nitrogen oxides

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.



Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component CAS-No. Value Control parameters Tetrahydro-2H- 1,4-oxazine Remarks Remarks Not classifiable as a human carcinogen Danger of cutaneous absorption TWA 20 ppm TWA CONTAMINATION TWA 20 ppm TWA CONTAMINATION TWA CONTAMINATION Skin notation STEL Skin notation STEL Skin notation STEL Skin notation STEL California permissible exposure limits for chemical contaminants (Title 8, Article	ingredients with workplace control parameters						
Tetrahydro-2H- 1,4-oxazine Remarks Not classifiable as a human carcinogen Danger of cutaneous absorption TWA 20 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 30 ppm 105 mg/m3 Exposure Limits Potential for dermal absorption TWA 20 ppm 30 ppm 105 mg/m3 Exposure Limits Potential for dermal absorption TWA 20 ppm 70 mg/m3 USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 20 ppm 70 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm 70 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation SKin notation STEL 30 ppm 105 mg/m3 California permissible exposure limits for chemical	Component	CAS-No.	Value	Control	Basis		
Remarks Not classifiable as a human carcinogen Danger of cutaneous absorption TWA 20 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 30 ppm USA. NIOSH Recommended 105 mg/m3 Exposure Limits Potential for dermal absorption TWA 20 ppm USA. Occupational Exposure 105 mg/m3 USA. OSHA - Table Z-1 105 mg/m3 for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits 105 mg/m3 for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits 105 mg/m3 for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits 105 mg/m3 for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure limits for chemical				parameters			
Remarks Not classifiable as a human carcinogen Danger of cutaneous absorption TWA 20 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 30 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 20 ppm USA. Occupational Exposure TWA 20 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 California permissible exposure limits for chemical	Tetrahydro-2H-	110-91-8	TWA	20 ppm	USA. ACGIH Threshold Limit		
Remarks Not classifiable as a human carcinogen Danger of cutaneous absorption TWA 20 ppm 70 mg/m3 Exposure Limits Potential for dermal absorption ST 30 ppm 105 mg/m3 Exposure Limits Potential for dermal absorption TWA 20 ppm 70 mg/m3 Exposure Limits Potential for dermal absorption TWA 20 ppm 70 mg/m3 Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm 70 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm 105 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm 105 mg/m3 California permissible exposure limits for chemical					Values (TLV)		
Danger of cutaneous absorption TWA 20 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 30 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 20 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure limits for chemical	,				,		
Danger of cutaneous absorption TWA 20 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 30 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 20 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure limits for chemical		Remarks					
TWA 20 ppm							
70 mg/m3 Exposure Limits							
Potential for dermal absorption ST 30 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 20 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation SKin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation SKIN notation STEL 30 ppm California permissible exposure limits for chemical			1 007 (
ST 30 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 20 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure limits for chemical			Potential fo				
105 mg/m3 Exposure Limits							
Potential for dermal absorption TWA 20 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation SKIN notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure limits for chemical			51	1			
TWA 20 ppm			5				
TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants TWA 20 ppm June 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 SKIN notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure limits for chemical							
Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation Skin notation SKin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical			TWA				
Skin designation TWA 20 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical				70 mg/m3			
TWA 20 ppm					Limits for Air Contaminants		
70 mg/m3 for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical			Skin designation				
To mg/m3 for Air Contaminants - 1910.1000			TWA	20 ppm	USA. OSHA - TABLE Z-1 Limits		
Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical					for Air Contaminants -		
Skin notation STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical				J, -			
STEL 30 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical							
105 mg/m3 for Air Contaminants - 1910.1000 Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical					USA, OSHA - TABLE 7-1 Limits		
Skin notation STEL 30 ppm California permissible exposure limits for chemical			0.22	1			
Skin notation STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical				103 1119/1113			
STEL 30 ppm California permissible exposure 105 mg/m3 limits for chemical			Skin notati	n On	1910.1000		
105 mg/m3 limits for chemical					California normiccible expecure		
			SIEL				
				105 mg/m3			
107)					10/)		
Skin				T			
PEL 20 ppm California permissible exposure			PEL	1			
70 mg/m3 limits for chemical				70 mg/m3	limits for chemical		
contaminants (Title 8, Article					contaminants (Title 8, Article		
107)							
Skin			Skin				

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles



Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 60 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid Color: colorless

b) Odor ammoniacalunpleasant

c) Odor Threshold No data available

d) pH 10.6 at 5 g/l at 20 °C (68 °F)

e) Melting point/range: -7 - -5 °C (19 - 23 °F)

point/freezing point

and boiling range

f) Initial boiling point 127 - 129 °C 261 - 264 °F at 1,013.25 hPa

g) Flash point 31 °C (88 °F) - closed cup

h) Evaporation rate No data available

i) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 10.8 %(V)



flammability or Lower explosion limit: 1.8 %(V)

explosive limits

k) Vapor pressure 9.33 hPa at 20 °C (68 °F)

41.32 hPa at 38 °C(100 °F)

I) Vapor density 3.01 - (Air = 1.0)

m) Relative density 1.001 at 20 °C (68 °F)

n) Water solubility completely miscible

o) Partition coefficient: log Pow: -2.55 at 25 °C (77 °F) - Bioaccumulation is not

n-octanol/water expected.

p) Autoignition 255 °C (491 °F) at 1,013 hPa - DIN 51794

temperature

q) Decomposition > 330 °C (> 626 °F) -

temperature

r) Viscosity 2.2 mm2/s at 20 °C (68 °F) -

s) Explosive properties No data available

t) Oxidizing properties No data available

9.2 Other safety information

Dissociation constant 8.49 at 25 °C (77 °F)

Relative vapor 3.01 - (Air = 1.0)

density

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

Strong oxidizing agents

Nitriles

acids

Caution! In contact with nitrites, nitrates, nitrous acid possible liberation of nitrosamines!

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Aluminum, nonferrous metals

10.6 Hazardous decomposition products

In the event of fire: see section 5



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 1,900 mg/kg

(OECD Test Guideline 401)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of

perforation of the esophagus and the stomach. Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l

(Expert judgment)

LD50 Dermal - Rabbit - male - 500 mg/kg

(OECD Test Guideline 402)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 3 min (OECD Test Guideline 404)

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye damage.

(OECD Test Guideline 405) Causes serious eye damage.

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative

Remarks: (IUCLID)

Germ cell mutagenicity

Ames test

Escherichia coli/Salmonella typhimurium

Result: Positive results were obtained in some in vitro tests.

Remarks: (ECHA)

In vitro mammalian cell gene mutation test

Mouse lymphoma test Result: negative

sister chromatid exchange assay Chinese hamster ovary cells

Result: negative

unscheduled DNA synthesis assay

rat hepatocytes Result: negative

Hamster - female Result: negative

Remarks: (ECHA)

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.



NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Acute oral toxicity - If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Not available

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Toxic effect on:

Liver

Kidney

Under given conditions, contact with nitrites or nitric acid can lead to the formation of nitrosamines, which have shown themselves to be carcinogenic in animal experiments.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish static test LC50 - Oncorhynchus mykiss (rainbow trout) - 180 mg/l -

96 h

Remarks: (in soft water)

(Lit.)



Toxicity to daphnia and other aquatic

static test EC50 - Daphnia magna (Water flea) - 44.5 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae

invertebrates

static test ErC50 - Skeletonema costatum - 9 mg/l - 72 h

(ISO 10253)

Toxicity to bacteria

static test EC20 - activated sludge - > 1,000 mg/l - 30 min

(OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 25 d

Result: 93 % - Readily biodegradable.

(OECD Test Guideline 301E)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 42 d

at 25 °C - 0.5 mg/I(Tetrahydro-2H-1,4-oxazine)

Bioconcentration factor (BCF): < 2.8

(OECD Test Guideline 305C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Forms corrosive mixtures with water even if diluted.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and loc No mixing with other waste. Handle uncleaned containers like the product See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 2054 Class: 8 (3) Packing group: I

Proper shipping name: Morpholine

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 2054 Class: 8 (3) Packing group: I EMS-No: F-E, S-C

Proper shipping name: MORPHOLINE



IATA

UN number: 2054 Class: 8 (3)

Proper shipping name: Morpholine

Packing group: I

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

DISCLAIMER OF RESPONSIBILITY

The information on this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable.

Version: 8.0 Revision Date: 02/18/2021 Print Date: 03/13/2021

