



SILVER FERN
CHEMICAL INC

SILVER FERN CHEMICAL

Safety Data Sheet

n-Butanol

SECTION 1 Product and Company Identification

Trade name n-Butanol

Synonyms Butyl Alcohol, 1-Butanol

Use Fuel additive, Industrial use, Intermediate, Oilfield, Paint and Coatings, Process/Extraction Solvent, Raw material for chemical processes, Raw material for industry, Solvent

Company Silver Fern Chemical, Inc
2226 Queen Anne Avenue North
Seattle WA, 98109, USA
1-866-282-3384

Business Contact:
Customer Service: 1-866-282-3384
info@silverfernchemical.com

24 Hour Emergency **Infotrac: 1-800-535-5053 (USA & Canada)**
Outside USA & Canada 1-352-323-3500

SECTION 2 HAZARDS IDENTIFICATION

OSHA/GHS Hazards	Flammable liquids	Category 3
	Acute toxicity (Oral)	Category 4
	Serious eye damage	Category 1
	Skin irritation	Category 2
	Specific target organ toxicity - single exposure	Category 3 (Narcotic effects)
	Specific target organ toxicity - single exposure	Category 3 (Resp. irritation)

LABEL ELEMENTS

Hazard symbols



Signal word Danger

Hazard statements H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.



- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

Precautionary statements

- Prevention**
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 - P240 Ground/bond container and receiving equipment.
 - P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 - P242 Use only non-sparking tools.
 - P243 Take precautionary measures against static discharge.
 - P280 Wear protective gloves/ eye protection/ face protection.
 - P264 Wash skin thoroughly after handling.
 - P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
- Response**
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 - P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 - P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.
 - P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
 - P330 Rinse mouth.
 - P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Storage**
- P403 + P405 + P235 Store locked up in a well-ventilated place. Keep cool.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
1-Butanol	71-36-3	>=99

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

SECTION 4 FIRST AID MEASURES

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.



- Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.
- Ingestion** If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

SECTION 5 FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Fire/explosion Flash back possible over considerable distance. NFPA Class II combustible liquid.

Suitable extinguishing media Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO₂)

Protective equipment and precautions for firefighters Wear self-contained breathing apparatus and protective suit. Keep containers and surroundings cool with water spray.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up Evacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system.

Spill precautions Material can create slippery conditions.

SECTION 7 HANDLING AND STORAGE

Safe handling advice Ensure all equipment is electrically grounded before beginning transfer operations.

Storage/Transport pressure Ambient

Load/Unload temperature Ambient

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Ensure adequate ventilation, especially in confined areas.



PERSONAL PROTECTIVE EQUIPMENT

Eyes Wear as appropriate: Goggles, Face-shield

Skin Wear suitable protective clothing, gloves and eye/face protection.

Inhalation Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection.

EXPOSURE GUIDELINES

Components Exposure limit(s)

1-Butanol OSHA PEL (Permissible Exposure Limit) 100 ppm 300 mg/m³
ACGIH TLV (8-hour) 20 ppm

*Skin Hazard: Skin exposure should be prevented or reduced to control skin absorption.

PEL= Permissible Exposure Limits
TLV= Threshold Limit Value
EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)
STEL= Short Term Exposure Limit (15 min.)
WEEL= Workplace Environmental Exposure Level

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid;

Colour colourless

Form liquid

Odour sweet pungent

Odour Threshold No data available

Flash point 38 °C, 100 °F; ASTM D 93;

Flammability Upper explosion limit: 11.2 %(V)
Lower explosion limit: 1.4 %(V)

Boiling point/boiling range 117 °C, 242 °F;

Melting point/range -89 °C, -128 °F;

Auto-ignition temperature 343 °C, 649 °F;

Decomposition temperature No data available



Flammability (solid, gas)	No data available
Vapour pressure	4.5 mm Hg @ 25 °C, 78 °F;
Vapour density	2 - 3
Density	0.805 g/cm ³ @ 27 °C, 80 °F;
Specific gravity	No data available
Water solubility	7.8 g/100g partly soluble
Viscosity	4 cSt @ 20 °C, 68 °F;
pH	No data available
Evaporation rate	No data available
Partition coefficient: n-octanol/water	No data available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.
Conditions to avoid	Keep away from heat and sources of ignition.
Hazardous decomposition products	Combustion products include carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.
Materials to avoid	Can react with strong oxidizers, inorganic acids, and halogens.
Hazardous polymerisation	None.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute dermal toxicity	LD50 Rabbit: 2,000 - 5,300 mg/kg
Acute inhalation toxicity	LC50 Rat (4 hours): 7.4 mg/l
Acute oral toxicity	LD50 Rat: 300 - 2,000 mg/kg



Skin corrosion/irritation	Primary irritation (Rabbit): 24 hours; 1.4 (Max. score is 8.0.)
Serious eye damage/eye irritation	Primary irritation (Rabbit): 27.3 (Max. score is 110.)
Respiratory or skin sensitisation	No data available
Germ cell mutagenicity	Genotoxicity in vitro: No data available Genotoxicity in vivo: No data available Assessment Mutagenicity: No data available
Reproductive toxicity	Reproductive toxicity: No data available Assessment Reproductive toxicity: No data available Teratogenicity: No data available Assessment teratogenicity: No data available
STOT - single exposure	No data available
STOT - repeated exposure	No data available
Aspiration toxicity	No data available
Carcinogenicity	Assessment carcinogenicity: Contains no ingredient listed as a carcinogen

SECTION 12 ECOLOGICAL INFORMATION

Aquatic toxicity Non-toxic to aquatic life.

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)) 96 hours: 1,376 mg/l



Toxicity to aquatic invertebrates	EC50 (Daphnia magna (Water flea)) 48 hours: 1,328 mg/l
Toxicity to algae	ErC50 (Pseudokirchneriella subcapitata (green algae)) 96 hours: 225 mg/l
Chronic toxicity to fish	No data available
Chronic toxicity to aquatic invertebrates	No data available
Biodegradation	Readily biodegradable. Closed Bottle test (20 d): 92 %
Bioaccumulative potential	No data available
Mobility in soil	No data available
Other adverse effects	No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Code	D001 - Ignitability (RQ 100 LB). Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification.
Disposal methods	Land disposal of this product is restricted. Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.
Empty containers.	Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

SECTION 14 TRANSPORT INFORMATION

DOT	UN 1120, Butanols, 3, III When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.
------------	---



IATA UN 1120, Butanols, 3, III
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

IMDG UN 1120, Butanols, 3, III
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks No data available

SECTION 15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA Inventory Listing

Components

1-Butanol

CAS-No.

71-36-3

SARA 302 Status

Components

CAS-No.

Weight percent

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Classification

"Immediate (acute) health hazard", "Fire hazard"

SARA 313 Chemical

Components

1-Butanol

CAS-No.

71-36-3

Weight percent

>= 99 %

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

1-Butanol

Reportable Quantity

5,000 LB

Weight percent

>= 99 %



INTERNATIONAL REGULATIONS

WHMIS Classification

Flammable liquids	Category 3
Acute toxicity (Oral)	Category 4
Serious eye damage	Category 1
Skin irritation	Category 2
Specific target organ toxicity - single exposure	Category 3 (Narcotic effects)
Specific target organ toxicity - single exposure	Category 3 (Resp. irritation)

European Union

Classification according to Regulation (EU) 1272/2008.

Flammable liquids, Category 3
Acute toxicity (Oral), Category 4
Serious eye damage, Category 1
Skin irritation, Category 2
Specific target organ toxicity - single exposure, Category 3 (Narcotic effects)
Specific target organ toxicity - single exposure, Category 3 (Resp. irritation)

Australia. Inventory of Chemical Substances (AICS)	Listed
Japan. Inventory of Existing and New Chemical Substances (ENCS)	Listed
Japan. ISHL - Inventory of Chemical Substances	Listed
Canada. Domestic Substances List (DSL) Inventory	Listed
Canada. Non-Domestic Substance Listing (NDSL)	Not listed
Philippines. Inventory of Chemicals / Chemical Substances (PICCS)	Listed
Korea. Existing Chemicals Inventory (KECI)	Listed
China. Inventory of Existing Chemical Substances (IECSC)	Listed
Mexico	Listed
New Zealand. Inventory of Chemical Substances	Listed
Switzerland	Listed
Taiwan. National Existing Chemical Inventory (NECI)	Listed



Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

STATE REGULATIONS

California Prop. 65

Components

none

CAS-No.

SECTION 16 OTHER INFORMATION

HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Physical Hazard/ Instability</u>
HMIS®	3	2	0
NFPA	3	2	0

DISCLAIMER OF RESPONSIBILITY

The information on this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable.